

Lesson 03

Do-loop

A loop allows for a set of instructions to be executed over and over again.

```
Do[ Print[ "hello" ], { k, 1, 4 } ]
```

```
Do[  
Print[ "hello" ]  
, { k, 1, 4 } ]
```

```
Do[  
Print[ "hello" ] ;  
, { k, 1, 4 } ] ;
```

```
Do[  
Print[ k^2 ]  
, {k, 1, 4} ]
```

(* *Mathematica* does not understand what I want to do below. I need to separate the lines with semicolons *)

```
Do[  
a=k^2  
Print[ a ]  
, {k, 1, 4} ]
```

(* These alternatives will be fine *)

```
Do[  
a=k^2;  
Print[ a ]  
, {k, 1, 4} ]
```

```
Do[  
a=k^2 ;  
Print[ a ] ;  
, {k, 1, 4} ]
```

(* More general examples *)

```
Clear[ a, b, ab ] ;  
Do[  
a = k^2 ;  
b = 1 + k ;  
ab = a*b ;  
Print[ { a, b, ab } ] ;  
, { k, 1, 4 } ] ;
```

```
Clear[ a, b, ab ] ;  
Do[
```

```

a[ k ] = k^2 ;
b[ k ] = 1 + k ;
ab[ k ] = a[ k ]*b[ k ] ;
Print[ { a[ k ], b[ k ], ab[ k ] } ] ;
, { k, 1, 4 } ] ;

```

```
a[ 2 ] +ab[ 4 ]
```

-) Construct a vector with 5 elements, where they are all zero.

```

Clear[vec]
vec= Table[ 0, {k,1,5} ]

```

```

Clear[ elem, vec ];
Do[ elem[k] = 0, {k, 1, 5} ];
vec = Table[ elem[ k ], {k, 1, 5} ]

```

-) Construct a vector with 30 elements, such that the first and last elements are equal to 10, the remaining elements at even positions are equal to 2 and the remaining elements at odd positions are equal to -1.

```

Clear[ elem, vec ];
elem[ 1 ] =10;
elem[ 30 ] =10;
Do[ elem[ k ] = 2, { k, 2, 28, 2} ];
Do[ elem[ k ] = - 1, { k, 3, 29, 2} ];
vec = Table[ elem[ k ], { k , 1, 30 } ]

```

-) Construct a 5 X 5 upper triangular matrix of 1s with 0s below the main diagonal.

```

Clear[ elem, triang ];
Do[ Do[ elem[ j, k ] = 0, { k, 1, 5 } ], { j, 1, 5 } ];
Do[ Do[ elem[ j, k ] = 1, {k, j, 5 } ], { j, 1, 5 } ];
triang = Table[ Table[ elem[ j, k ], { k, 1, 5 } ], { j, 1, 5 } ];
MatrixForm[ triang ]

```

-) Given the matrix

```

Clear[m1];
m1 = { { 1, 2, 3, 4 }, { 1, 2, 3, 4 }, { 1, 2, 3, 4 } };
MatrixForm[ m1 ]

```

```

tm1 = Transpose[ m1 ];
MatrixForm[ tm1 ]

```

Use do-loops to compute its transpose

```

Clear[ mt, mTrans];
Do[
Do[
mt[ j, k] = m1[ [ k, j ]];
, { k, 1, 3 } ];
, { j, 1, 4 } ];
mTrans = Table[ Table[ mt[ j, k ], { k, 1, 3 } ], { j, 1, 4 } ];
MatrixForm[ mTrans ]
MatrixForm[ Transpose[ m1 ] ]

```

If-Then-Else statement

■ If[condition, true, false]

```
-) Clear[a];
a=2;
If[ a>0, Print[ " a is positive "], Print[ " a is negative " ] ]
```

```
-) Construct a 5 X 5 upper triangular matrix of 1s with 0s below the main diagonal.
Clear[ triag ];
triag = Table[ Table[ If[ k >= j, 1, 0 ], { k, 1, 5 } ], { j, 1, 5 } ];
MatrixForm[ triag ]
```

```
-) Define a function g[ x ] which returns x/2 if x is even and 3 x + 1 if x is odd
Clear[g, x];
g[ x_ ] := If[ Mod[ x, 2 ] == 0, x/2, 3 x + 1 ];
g[ 4 ]
g[ 3 ]
```

```
-) Define a function h[ x ] which is 1 when x>0, -1 when x<0, and 0 at x=0. Here we nest the If-function
Clear[h, x];
h[ x_ ] := If[ x>0, 1, If[ x<0, -1, 0 ] ];
h[ 2 ]
h[ -3 ]
h[ 0 ]
```

```
-) Compute the total number of numbers between 1 and 20 which are NOT multiples of 2, 3 or 5.
Clear[ howmany ];
howmany = 0;
Do[
If[ Mod[ k, 2 ] != 0 && Mod[ k, 3 ] != 0 && Mod[ k, 5 ] != 0, howmany = howmany +1 ];
,{ k, 1, 20 } ]
Print[ "The total number is ", howmany];
```

```
-) Make a list with the numbers between 1 and 20 which are NOT multiples of 2, 3 or 5.
Clear[ howmany, num ];
howmany = 0;
Do[
If[ Mod[ k, 2 ] != 0 && Mod[ k, 3 ] != 0 && Mod[ k, 5 ] != 0, { howmany = howmany +1, num[ howmany ] = k } ];
,{ k, 1, 20 } ]
Table[ num[ k ], {k, 1, howmany } ]
```

Export and Import

Create a list with 10 pairs of even and odd numbers

```
Clear[ list ];
list = Table[ { k, k + 1}, { k, 2, 20, 2} ]
```

Export this list to file named "PairEvenOdd.dat" which should be placed in the same directory where you have been

saving your work.

First, check in which directory you currently are:

```
Directory[ ]
```

If this is not the one you want, set the correct one:

```
SetDirectory["Yeshiva"]
```

```
SetDirectory["ANGEL"]
```

```
SetDirectory["Presentations_Computational"]
```

Now we can export the data as

```
Export["PairEvenOdd.dat", list ]
```

Go to the folder and verify if it is really there. If it is, close *Mathematica* and restart it again.

Let us now import the data that we saved in the file `PairEvenOdd.dat`. Before doing that, we need to be sure again that we are in the correct directory. If so, then

```
Clear[ newlist ];
```

```
newlist = Import["PairEvenOdd.dat", "Table" ]
```

Try to solve the last problem of Assignment03 together in class.